

ACCOPPIATRICI ROTATIVE ROTATIVE COMBINING MACHINES

www.fratellialberti.com



A L B E R T I



DESCRIZIONE PRODOTTO:

Semplice da utilizzare e compatta, l'accoppiatrice rotativa **COMBI 46** è destinata ad applicazioni in cui è importante contenere spazio, volumi e costi.

Consente di accoppiare perfettamente materiali pre-incollati in continuo senza interruzioni di lavoro. Temperatura, tempi e pressioni sono regolabili all'interno di un vasto range.

PRODUCT DESCRIPTION:

Simple to use and compact, the **COMBI 46** rotary combining machine, has been developed specifically for those applications where it is very important to restrain the space, the volume and the labour cost. The **COMBI** machine allows to combine accurately pre-cemented materials without having idle timing characterizing the usage of the normal fusing heated plates, by using well defined temperatures, setting times and pressures.

FAV
ALBERTI

FRATELLI ALBERTI S.R.L.

Via Selene, 16 - 21100 Varese - Italia - Tel. +39 0332 333619
C.F. e PIVA 00197020126

🇮🇹 commerciale@fratellialberti.com

🇬🇧 export@fratellialberti.com

ACCOPPIATRICI ROTATIVE ROTATIVE COMBINING MACHINES

www.fratellialberti.com



A L B E R T I

CARATTERISTICHE MACCHINA:

- Temperatura regolabile (0-140°);
- Velocità nastro trasportatore regolabile (0-6 m/min);
- Pressione di accoppiatura regolabile (0-100 kg);
- Allineamento automatico del nastro;
- Nastro in teflon per una facile pulizia;
- Rullo riscaldatore rivestito in cromo a spessore per una superficie perfetta e resistente;
- Larghezza di lavoro 460, 650 e su richiesta 1000 mm;
- Tappeto anteriore per inserimento automatico e controllato dei componenti, opzionale.

DATI TECNICI:

HxLxP:

COMBI 46 128 x 90 x 90 cm

COMBI 65 128 x 110 x 90 cm

Peso netto:

COMBI 46 200 Kg

COMBI 65 260 Kg

Elementi riscaldanti:

COMBI46 3x1000 W

COMBI65 6x1000 W

Pressione Minima: 4 bar

MAIN FEATURES:

- Adjustable temperature (0-140°);
- Adjustable belt speed (0-6 m/min);
- Adjustable combining pressure (0-100 kg);
- Automatic belt alignment;
- Teflon belt to facilitate cleaning works;
- Even and long lasting surface Chromium plated heated roll;
- Working width 460, 650 and on request 1000 mm;
- Optional front belt for automatic feeding of the components.

TECHNICAL DATA:

HxLxP:

COMBI 46 128 x 90 x 90 cm

COMBI 65 128 x 110 x 90 cm

Net weight:

COMBI 46 200 Kg

COMBI 65 260 Kg

Heating Elements:

COMBI46 3 x 1000 W

COMBI65 6 x 1000 W

Minimum pressure: 4 bar

FAV
ALBERTI

#stayFAV

